




Product code	Color
3880-01-21	Mat white
3880-01-52	Silver

General specifications

Product type	: Ceiling lights
Mounting type	: Ceiling - surface
Description	: With reflector 120°
Indoor/outdoor lights	: Indoor
Applications	: Passage areas, Entrances, Corridors, Residential, Contract sector


Lighting specifications

Lamps description	: LED 1500lm 12W 3000K
Average lamp life (h)	: 50.000

Physical specifications

Body	: Die-cast aluminium
Finishes	: Polyester painted
Reflector	: High resistance faceted polycarbonate, high vacuum mirror metallized
Thermal Dissipation	: Passive

Electrical specifications



Driver availability	: Included
Driver mounting	: Integrated
Voltage (V)	: 230/240
Frequency (Hz)	: 50/60

Weight and dimensions

Height (mm)	: 39
External diameter (mm)	: 190
Weight (Kg)	: 0.7






Optical specifications

Light distribution	: Symmetric
Light emission	: Direct
Light beam (°)	: 120°



Lamps	Categories	Type	Wattage (W)	Lumens (lm)	Color Temp. (K)	CRI
	LED	COB LED	12	1500	3000	>85

Photometrics

3880-01 Gamma Angles 180° 120° 90° 75° 60° 45° 30° 15° 0° 15° 30° cd/klm	PF 19 LED 12W 1500 lm				R:100%				I.Max:361 Cd/Klm					
	H[m]	D[m]	Max lux	Med lux	Alpha=123°	H[m]	D[m]	Max lux	Med lux	Beta=123°	H[m]	D[m]	Max lux	Med lux
	1.00	3.70	463	87		1.00	3.76	463	87		1.00	3.76	463	87
	2.00	7.39	116	22		2.00	7.51	116	22		2.00	7.51	116	22
	3.00	11.09	51	10		3.00	11.27	51	10		3.00	11.27	51	10
	4.00	14.79	29	5		4.00	15.03	29	5		4.00	15.03	29	5
	5.00	18.48	19	3		5.00	18.79	19	3		5.00	18.79	19	3

Pictures and Applications

